

## PORTABLE CANNISTER BLOWER 8" DIAMETER

### Fan Dimensions:



### Fan Ratings:

Model #	PCC08A115E
HP	1/6
Hertz	60
RPM	3300
Volts	115
Phase	1
CFM* (free air)	731
dbA** @ 6'	74
dbA** @ 10'	70
WT.-LBS.	38

**Guard:** Bright Plated Steel, Inlet side, All openings less than 0.50"

**Motor:** Totally enclosed, Capacitor start, Continuous Duty, 10 foot three-wire cord with grounded plug

**Housing:** Heavy welded steel housing and cannister, Steel support base, Bright yellow powder coated, Comfort molded handle with steel handle on cannister. Shielded switch in handle.

**Propeller:** 7 Blades, die-cast aluminum propeller, with a airfoil design, clockwise rotation as viewed from the motor side.

### Electrical Data:

Volts	115
Running Amps	1.7
Locked Rotor Amps	5.7



NOTE: Electrical and noise data are supplied by the motor and propeller manufacturers, respectively. These values have not been independently verified by California Turbo, Inc. California Turbo, Inc. reserves the right to make product changes from time to time, without prior notification.

Call Sharpe Heating and Ventilating today for details and product offerings

Phone: (562) 695-5221 / Email: [sharpe@dmghvac.com](mailto:sharpe@dmghvac.com)